

## 82302B- NOR - 1/2 Ton High Lift Wheel Dolly



**Brand:** Norco  
**Product Code:** NOR-82302B  
**Call for Price:** 877-805-1154

### Short Description

### INTENDED USE:

For the removal and installation of single, tandem and duplex tires and wheels which are mounted on trucks that are supported above ground level.

### FEATURES:

- Heavy duty lift arms made with ball bearing conveyer rollers which allow easy rotation of wheels for alignment with bolt pattern.
- 7-1/2" of side to side lift arm adjustment eliminates the trial and error method of aligning the rim's lug holes with the wheel drum.

- A 1,500 pound capacity heavy duty winch with 5 to 1 gear ratio provides ease of operation.
- The winch gear design acts as a brake and allows the load to be lowered incrementally if desired and without the need for constant hand pressure against the crank handle.
- A hydraulic jack tilts the lift arms to match the angle of the spindle.
- Safety chain provided to secure tires and wheels to the dolly.
- Maneuverability is made easy by means of two rear mounted ball bearing caster wheels. The caster wheels include a locking mechanism which can prevent the dolly from moving.

## **Description**

For the removal and installation of single, tandem and duplex tires and wheels which are mounted on trucks that are supported above ground level.

## **FEATURES:**

- Heavy duty lift arms made with ball bearing conveyer rollers which allow easy rotation of wheels for alignment with bolt pattern.
- 7-1/2" of side to side lift arm adjustment eliminates the trial and error method of aligning the rim's lug holes with the wheel drum.
- A 1,500 pound capacity heavy duty winch with 5 to 1 gear ratio provides ease of operation.
- The winch gear design acts as a brake and allows the load to be lowered incrementally if desired and without the need for constant hand pressure against the crank handle.
- A hydraulic jack tilts the lift arms to match the angle of the spindle.
- Safety chain provided to secure tires and wheels to the dolly.
- Maneuverability is made easy by means of two rear mounted ball bearing caster wheels. The caster wheels include a locking mechanism which can prevent the dolly from moving.

## Specifications

### DIMENSIONS:

<b>Lift Height</b>	
Low	3"
High	41.25"
<b>Lift Arms</b>	
Width	24.25"
Length	21"
Tilt Angle	-2° to +30°
<b>Side to Side Adj.</b>	
Left	3.25"
Right	4.25"
<b>Overall Dimensions</b>	
Length	45.75"
Width	43.75"
Height	62"
<b>Shipping Weight</b>	315 lbs.

**\*PLEASE GIVE US CALL SO WE MAY PROVIDE YOU AN ACURATE SHIPPING QUOTE. AUTOMATED SYSTEM CANNOT PROVIDE ACURATE PRICING FOR SHIPMENTS WEIGHING OVER 100 LBS\***