72475A - NORCO - 3/4 Ton Telescopic Air/Hydraulic Transmission J



Brand: Norco

Product Code: NOR-72475A **Call for Price**: 877-805-1154

Phone: 877-805-1154 - Email: parts@automotive-lift.com

Short Description

72475A - NORCO - 3/4 Ton Telescopic Air/Hydraulic Transmission Jack

Designed for the removal, installation and transportation (in the lowered position) of transmissions and transfer cases on passenger cars, vans and light trucks that are raised by an in-ground or above-ground lift.

FEATURES:

- U.S. Patent No. 7,171,807
- Air/hydraulic foot pump provides hands free operation and easy, convenient lifting.
- Metered pump valve provides safe lowering of load.
- Fully adjustable universal saddle with hand adjustable corner brackets and safety chain.
- Safety overload system prevents jack from being used beyond its rated capacity.
- Two-stage flash chromed rams inhibit rust from entering hydraulic system.
- Wide base with four easy rolling 4" diameter swivel ball bearing caster wheels

(two are locking caster wheels) provides stability and easy maneuvering in its lowered position. The polyurethane wheels provide protection for expensive tile and epoxy floors.

- Comes with a larger 10-1/4" x 15-1/8" saddle plate and four adjustable "L"-shaped locating bars.
- Polyurethane wheels provide protection for expensive tile and epoxy floors.

Description

72475A - NORCO - 3/4 Ton Telescopic Air/Hydraulic Transmission Jack

Designed for the removal, installation and transportation (in the lowered position) of transmissions and transfer cases on passenger cars, vans and light trucks that are raised by an in-ground or above-ground lift.

FEATURES:

- U.S. Patent No. 7,171,807
- Air/hydraulic foot pump provides hands free operation and easy, convenient lifting.
- Metered pump valve provides safe lowering of load.
- Fully adjustable universal saddle with hand adjustable corner brackets and safety chain.
- Safety overload system prevents jack from being used beyond its rated capacity.
- Two-stage flash chromed rams inhibit rust from entering hydraulic system.
- Wide base with four easy rolling 4" diameter swivel ball bearing caster wheels (two are locking caster wheels) provides stability and easy maneuvering in its

lowered position. The polyurethane wheels provide protection for expensive tile and epoxy floors.

- Comes with a larger 10-1/4" x 15-1/8" saddle plate and four adjustable "L"-shaped locating bars.
- Polyurethane wheels provide protection for expensive tile and epoxy floors.