

# 910130A - Norco 10,000 PSI Air/Hydraulic Foot Pump



**Brand:** Norco  
**Product Code:** NOR-910130A  
**Call for Price:** 877-805-1154

## Short Description

For automotive / truck, industrial & construction jobs. The added convenience of an air motor reduces pumping time and effort to activate cylinders.

## FEATURES:

- Designed to utilize exhaust air to help power the pump, requiring only 80 p.s.i. air pressure to develop 10,000 p.s.i. hydraulic pressure.
- Air exhaust muffler for quieter operation.
- Air and oil inlet filters for reduced risk of damage from contamination.
- Designed with durable light weight, corrosion resistant plastics.
- Foot pedal provides hands free pumping and release of load.
- Designed to be used with a single-acting cylinder.
- Internal pressure relief valve for overload protection.
- Equipped with a more durable aluminum reservoir.
- Comes with two different size poppit valves that can be quickly and easily installed. Poppit valves reduce the return flow of oil back to the pump's reservoir providing a safer controlled lowering of load.

## Description

**For automotive / truck, industrial & construction jobs. The added convenience of an air motor reduces pumping time and effort to activate cylinders.**

#### **FEATURES:**

- Designed to utilize exhaust air to help power the pump, requiring only 80 p.s.i. air pressure to develop 10,000 p.s.i. hydraulic pressure.
- Air exhaust muffler for quieter operation.
- Air and oil inlet filters for reduced risk of damage from contamination.
- Designed with durable light weight, corrosion resistant plastics.
- Foot pedal provides hands free pumping and release of load.
- Designed to be used with a single-acting cylinder.
- Internal pressure relief valve for overload protection.
- Equipped with a more durable aluminum reservoir.
- Comes with two different size poppit valves that can be quickly and easily installed. Poppit valves reduce the return flow of oil back to the pump's reservoir providing a safer controlled lowering of load.

#### **Specifications**

P.S.I.: 10,000

Usable Oil Cap (Cu. In.): 122

Output Flow Rate with Load: 80.5

Output Flow Rate No Load:12.8

P.S.I Range: 70-170

Air Consumption (scfm): 24

Valve Function: Advance/Hold/Retract

Sound Level (Dba): 85

Thread Connections (Air NPT): .25"-18

Thread Connections (Hydraulic NPT): .375"-18

Dimensions (Inches)

Length:12.5"

Width: 5.75"

Height: 8"

Weight: 22lbs